

■ Features:

- Miniature size
- Available on tape and reel for automatic insertion
- Lead free part available

■ Applications:

- DC to DC converters for portable equipment , camcorder , LCD television set , digital camera , P.D.A., notebook

Dimensions in mm

| TYPE | A | B | C |
|---------|---------|---------|---------|
| SPS 418 | 4.7±0.5 | 4.7±0.5 | 2.0 Max |
| SPS 428 | 4.7±0.5 | 4.7±0.5 | 3.0 Max |

■ Specifications


| Inductance | SPS 418 | | SPS 428 | |
|------------|---------|--------|---------|--------|
| | DCR | Irms | DCR | Irms |
| TYPE | uH | (Ω)Max | (A)Max | (Ω)Max |
| 1R0N | 1.0 | 0.045 | 1.72 | |
| 1R2N | 1.2 | | | 0.024 |
| 1R8N | 1.8 | | | 0.028 |
| 2R2N | 2.2 | 0.075 | 1.32 | 0.031 |
| 2R7N | 2.7 | 0.105 | 1.28 | 0.043 |
| 3R3N | 3.3 | 0.110 | 1.04 | 0.049 |
| 3R9N | 3.9 | 0.155 | 0.88 | 0.065 |
| 4R7N | 4.7 | 0.162 | 0.84 | 0.072 |
| 5R6N | 5.6 | 0.170 | 0.80 | 0.101 |
| 6R8N | 6.8 | 0.200 | 0.76 | 0.109 |
| 8R2N | 8.2 | 0.245 | 0.68 | 0.118 |
| 100M | 10 | 0.200 | 0.61 | 0.283 |
| 120M | 12 | 0.210 | 0.56 | 0.132 |
| 150M | 15 | 0.240 | 0.50 | 0.149 |
| 180M | 18 | 0.338 | 0.48 | 0.166 |
| 220M | 22 | 0.397 | 0.41 | 0.235 |
| 270M | 27 | 0.441 | 0.35 | 0.261 |
| 330M | 33 | 0.694 | 0.32 | 0.378 |
| 390M | 39 | 0.709 | 0.30 | 0.384 |
| 470M | 47 | 0.922 | 0.28 | 0.587 |
| 560M | 56 | 1.080 | 0.26 | 0.625 |
| 680M | 68 | 1.300 | 0.24 | 0.699 |
| 820M | 82 | 1.550 | 0.22 | 0.915 |
| 101M | 100 | 1.730 | 0.20 | 1.020 |
| 121M | 120 | 2.390 | 0.18 | 1.270 |
| 151M | 150 | 2.670 | 0.15 | 1.350 |
| 181M | 180 | 4.000 | 0.14 | 1.540 |
| 221M | 220 | | | 1.720 |
| 271M | 270 | | | 1.950 |
| 331M | 330 | | | 2.660 |
| | | | | 0.14 |

■ Parts code:

SPS 418 — 150 — M

Type Inductance code Tolerance

■ Recommended Land Pattern:



| Type | A | B | C |
|---------|-----|-----|-----|
| SPS 418 | 5.3 | 1.5 | 1.9 |
| SPS 428 | 5.3 | 1.5 | 1.9 |

■ Notes:

- 1.Test Freq. :100KHz / 0.1V
- 2.PACKAGING: 2000Pcs/Reel
- 3.Tolerance: M=±20% , N=±30%
- 4.Operating temperature range:-40~+105°C

■ The current when the inductance becomes 35% lower than its

initial value or the actual current when the temperature of coil increases to $\Delta T=40^{\circ}\text{C}$.